


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 16.5/85 - 24 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO |
| VERSIÓN | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 155 A8 |
| LI/SS FREE ROLLING | 168 A8 |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94034741 | RC (IN) | 158.0 |
| SW (IN) | 16.3 | RIM REC | W 13 |
| OD (IN) | 52.2 | RIM ALT | W 14 L; W 15 L |
| SLR (IN) | 23.0 | ECE | E4-106R-001877 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 55 |
|-----------|-------|
| 5 FR | 17280 |
| 15 FR | 14690 |
| 20 FR | 13820 |
| 25 FR | 12350 |
| 5 DW | 11960 |
| 15 DW | 10160 |
| 20 DW | 9570 |
| 25 DW | 8540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.