


AGRIMAX SPARGO

TIRE SIZE	VF 380/90 R 54
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	176 D



DIMENSIONS IS STANDARD

SW (MM)	383	RIM REC	W13
OD (MM)	2056	RIM ALT	DW 13; DW 12; W 12
SLR (MM)	948	ECE	E11-106R-0010081
RC (MM)	6232	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2825	3155	3550	3875	4075	4270	4400	5430	4760	4990	5190	5385	5550	5715	5880	6040	6305	6565
FROM 65 TO 40	3055	3410	3835	4190	4405	4615	4760	4900	5150	5400	5610	5825	6000	6180	6355	6535	6820	7100
30	3120	3480	3915	4275	4495	4710	4855	5000	5255	5510	5725	5945	6125	6305	6485	6670	6960	7245
20	3180	3545	3990	4360	4580	4805	4950	5100	5355	5615	5835	6060	6245	6425	6610	6795	7090	7385
10	3360	3750	4220	4610	4845	5080	5235	5390	5665	5940	6170	6405	6600	6795	6990	7190	7500	7810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.