


AT 603

TIRE SIZE	10.5/80 - 18
UM	IS STANDARD
CONSTRUCTION	 BIAS
MACHINERY	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ЭКСКАВАТОР- ПОГРУЗЧИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ЭКСКАВАТОР- ПОГРУЗЧИК
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	274	RIM REC	W 9
OD (MM)	907	RIM ALT	W 8; 9
SLR (MM)	422	ECE	E11-106R-004546
RC (MM)	2727	PR	10

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	2730
25 FR	2320
30 FR	2185
40 FR	1950
10 DW	1905
25 DW	1620
30 DW	1525
40 DW	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.