

## AGRIMAX V-FLECTO

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TYRE SIZE</b>    | <b>VF 750/70 R 44</b>                                                                    |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HIGH-POWER TRACTOR / TRACTOR                                                             |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 186 D                                                                                    |



### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94066926 | <b>RC (IN)</b> | 253.9           |
| <b>SW (IN)</b>  | 29.9     | <b>RIM REC</b> | DW 25 B         |
| <b>OD (IN)</b>  | 85.6     | <b>RIM ALT</b> | DW 24 B         |
| <b>SLR (IN)</b> | 37.7     | <b>ECE</b>     | E11-106R-006765 |

### LOAD CAPACITY (LBS/TYRE)

| MPH / PSI                     | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
| 45                            | 9530  | 11060 | 12590 | 14300 | 15830 | 17350 | 19060 |
| FROM 40 TO 25                 | 10470 | 12150 | 13820 | 15710 | 17380 | 19060 | 20940 |
| 20                            | 10680 | 12400 | 14110 | 16030 | 17740 | 19440 | 21360 |
| 12                            | 10890 | 12640 | 14380 | 16340 | 18090 | 19830 | 21780 |
| 5                             | 11520 | 13370 | 15210 | 17280 | 19120 | 20960 | 23040 |
| *UPTO 5 CYC WITH FRONT LOADER | 14660 | 17010 | 19360 | 21990 | 24340 | 26690 | 29320 |
| 5 HT                          | 10680 | 12400 | 14110 | 16030 | 17740 | 19440 | 21360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.