


RIDEMAX FL 693 M



| | |
|--------------|--|
| TIRE SIZE | 600/55 R 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA |
| VERSIÓN | HD |
| TIRE TYPE | TL |
| LI/SS | 177 D |

DIMENSIONES IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1333 | ECE | E11-106R-003007 |
| SLR (MM) | 586 | SRI | 625 |
| RC (MM) | 4077 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 | 6.0 |
|------------|------|------|------|------|------|------|------|-------|-------|-------|-------|
| 65 | 2265 | 2705 | 3285 | 3800 | 4380 | 4965 | 5330 | 5915 | 6500 | 6865 | 7300 |
| 50 | 2740 | 3270 | 3980 | 4595 | 5305 | 6010 | 6450 | 7160 | 7865 | 8305 | 8835 |
| 40 | 3080 | 3675 | 4470 | 5165 | 5960 | 6755 | 7250 | 8045 | 8840 | 9335 | 9930 |
| 30 | 3420 | 4080 | 4965 | 5735 | 6615 | 7500 | 8050 | 8935 | 9815 | 10365 | 11025 |
| 25 | 3580 | 4270 | 5195 | 6000 | 6925 | 7845 | 8425 | 9345 | 10270 | 10845 | 11535 |
| 10 | 4075 | 4865 | 5915 | 6835 | 7885 | 8940 | 9595 | 10645 | 11695 | 12355 | 13140 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.