

AGRIMAX RT 855

TIRE SIZE	180/95 R 16
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	105 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	185	RIM REC	5.5 F
OD (MM)	760	RIM ALT	6.0 F
SLR (MM)	340	ECE	E4-106R-000756
RC (MM)	2265	SRI	350

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	430	550	670	735	790	865	925	-
40	430	550	670	735	790	865	925	-
30	460	585	715	785	845	925	990	-
10	505	655	795	950	1085	1130	1255	1390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.