

# ROCK STAR IND4

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>14.00 - 24</b>                              |
| <b>UM</b>           | IS STANDARD                                    |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | MANIPULATOR DE CONTAINERE<br>GOALE / STIVUITOR |
| <b>VERSION</b>      | PORT INDUSTRIAL                                |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIUNI IS STANDARD

|                 |         |                 |      |
|-----------------|---------|-----------------|------|
| <b>OD (MM)</b>  | 1425    | <b>PR</b>       | 32   |
| <b>SLR (MM)</b> | 635     | <b>TRA CODE</b> | IND4 |
| <b>RC (MM)</b>  | 4350    |                 |      |
| <b>RIM REC</b>  | 10.00 W |                 |      |

## LOAD CAPACITY (KG/TIRE)

|                   |              |
|-------------------|--------------|
| <b>KM/H / BAR</b> | <b>10.00</b> |
| 10                | 14175        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.