

AGRIMAX FORCE

TIRE SIZE	IF 710/60 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	172 D



DIMENSIONES US STANDARD

CÓDIGO USA	94057511	RC (IN)	212.8
SW (IN)	27.9	RIM REC	DW 25 B
OD (IN)	71.5	ECE	E11-106R-004754
SLR (IN)	32.0	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5800	6680	7690	8580	9590	10470	11740	12630
FROM 40 TO 25	6380	7350	8470	9440	10550	11520	12910	13900
20	6640	7640	8800	9810	10970	11970	13410	14440
12	6890	7940	9140	10180	11390	12430	13930	14490
5	8100	9340	10750	11980	13390	14630	16390	17640
*UPTO 5 CYC WITH FRONT LOADER	8930	10280	11850	13200	14760	16130	18070	19440
5 HT	6640	7640	8800	9810	10970	11970	13410	14440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.