


AGRIMAX V- FLECTO



TIRE SIZE	VF 710/60 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	173 D

DIMENSÕES IS STANDARD

SW (MM)	708	RIM REC	DW 25 B
OD (MM)	1716	RIM ALT	DW 24 B; DW 27 B
SLR (MM)	752	ECE	E11-106R-007201
RC (MM)	5097	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3020	3490	3965	4500	4910	5325	5915
FROM 65 TO 40	3315	3835	4355	4940	5395	5850	6500
30	3385	3915	4445	5040	5505	5970	6630
20	3450	3990	4530	5140	5615	6085	6760
10	3650	4220	4795	5435	5935	6435	7150
*UPTO 10 CYC WITH FRONT LOADER	4645	5370	6100	6920	7555	8190	9100
10 HT	3385	3915	4445	5040	5505	5970	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.