

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 620/70 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 166 D |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 625 | RIM REC | DW 20 B |
| OD (MM) | 1935 | RIM ALT | DW 18 L |
| SLR (MM) | 876 | ECE | E11-106R-005998 |
| RC (MM) | 5801 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 2495 | 2865 | 3290 | 3710 | 4135 | 4560 | 4985 | 5300 |
| 50 | 2620 | 3010 | 3455 | 3900 | 4345 | 4790 | 5235 | 5565 |
| 40 | 2730 | 3135 | 3600 | 4065 | 4530 | 4995 | 5460 | 5805 |
| 30 | 2865 | 3295 | 3780 | 4270 | 4755 | 5245 | 5730 | 6095 |
| 10 LT | 3340 | 3840 | 4410 | 4975 | 5545 | 6115 | 6680 | 7105 |
| 10 HT | 2865 | 3295 | 3780 | 4270 | 4755 | 5245 | 5730 | 6095 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.