

# FLOTATION 648 T



<b>TIRE SIZE</b>	550/45 - 22.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	MOISSONNEUSE / MOISSONNEUSE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	147 A8/144 B
<b>LI/SS FREE ROLLING</b>	159 A8/156 B

## DIMENSIONS US STANDARD

<b>CODE USA</b>	94052066	<b>RC (IN)</b>	126.1
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	42.1	<b>PR</b>	16
<b>SLR (IN)</b>	18.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	35	38	41
5 FR	12350	12930	13500
10 FR	11110	11640	12160
20 FR	9880	10350	10800
25 FR	8820	9240	9640
30 FR	7940	8310	8820
5 DW	8670	9090	9490
10 DW	7800	8180	8540
20 DW	6930	7270	7590
25 DW	6190	6490	6780
30 DW	5580	5840	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.