

AGRIMAX V- FLECTO

VF 480/60 R 28

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 145 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 470 | RIM REC | DW 16 L |
| OD (MM) | 1290 | RIM ALT | W 16 L |
| SLR (MM) | 571 | ECE | E11-106R-005496 |
| RC (MM) | 3807 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|--------------------------------|------|------|------|------|------|------|
| 70 | 1450 | 1685 | 1920 | 2160 | 2395 | 2635 |
| FROM 65 TO 40 | 1595 | 1855 | 2115 | 2375 | 2635 | 2900 |
| 30 | 1625 | 1890 | 2155 | 2420 | 2685 | 2955 |
| 20 | 1655 | 1925 | 2195 | 2470 | 2740 | 3015 |
| 10 | 1750 | 2040 | 2325 | 2610 | 2895 | 3190 |
| *UPTO 10 CYC WITH FRONT LOADER | 2230 | 2595 | 2960 | 3325 | 3685 | 4060 |
| 10HT | 1625 | 1890 | 2155 | 2420 | 2685 | 2955 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.