


RIDEMAX IT 696

| | |
|---------------------|--|
| TIRE SIZE | 500/70 R 24 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATOR |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 164 A8 ; 159 D |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CÓDIGO USA | 94070244 | RC (IN) | 155.7 |
| SW (IN) | 19.8 | RIM REC | DW 16 L |
| OD (IN) | 51.6 | RIM ALT | DW 15 L; DW 18 L |
| SLR (IN) | 23.7 | ECE | E11-106R-007547 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|-------|-------|
| 40 | 3860 | 4730 | 5310 | 6270 | 7140 | 8010 | 8780 | 9640 |
| 30 | 4170 | 5110 | 5730 | 6780 | 7720 | 8650 | 9480 | 10420 |
| 25 | 4410 | 5400 | 6060 | 7160 | 8160 | 9150 | 10030 | 11020 |
| 20 | 4630 | 5680 | 6370 | 7530 | 8560 | 9610 | 10540 | 11570 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.