


AGRIMAX V-FLECTO

TIRE SIZE	VF 580/85 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	SPECIAL
TIRE TYPE	TL
LI/SS	183 D



DIMENSIONI US STANDARD

CODICE USA	94069408	RC (IN)	242.8
SW (IN)	23.9	RIM REC	DW20B
OD (IN)	81.0	RIM ALT	DW18B; MW20B
SLR (IN)	36.3	ECE	E11-106R-006444

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
45	7550	8770	10010	11230	12470	13690	15100	15970	17550
FROM 40 TO 25	8300	9640	11000	12350	13700	15050	16590	17560	19300
20	8740	9840	11220	12600	13980	15350	16930	17910	19680
12	8630	10030	11440	12840	14250	15650	17260	18260	20060
5	9130	10610	12100	13580	15070	16560	18250	19310	21220
UPTO 20 CYC	9410	10950	12490	14020	15550	17080	18830	19930	21890
UPTO 10 CYC	11240	13070	14900	16730	18560	20390	22490	23790	26130
UPTO 5 CYC	12320	14320	16320	18330	20340	22340	24640	26070	28640
5 HT	8470	9840	11220	12600	13980	15350	16930	17910	19680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.