

# RIB F3

**9.00 - 16**

|                     |   |
|---------------------|---|
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | TEK ÇEKER TRAKTÖR / RÖMORK /<br>TRAKTÖR / UYGULAMALI MAKINE |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |
|                     | 120 A6 ; 112 A8   |



## UNDEFINED US STANDARD

|                 |          |                |                    |
|-----------------|----------|----------------|--------------------|
| <b>USA CODE</b> | 94027781 | <b>RC (IN)</b> | 101.3              |
| <b>SW (IN)</b>  | 9.6      | <b>RIM REC</b> | W 8                |
| <b>OD (IN)</b>  | 34.6     | <b>RIM ALT</b> | 6.00 F; W 7; W 8 L |
| <b>SLR (IN)</b> | 15.2     | <b>ECE</b>     | E11-106R-004592    |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 68   |
|-----------|------|
| 20        | 3090 |
| 25        | 2470 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.