


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>210/95 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	106 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94028665	<b>RC (IN)</b>	94.0
<b>SW (IN)</b>	8.4	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	31.7	<b>RIM ALT</b>	W 6 ; 6 LB
<b>SLR (IN)</b>	14.2	<b>ECE</b>	E4-106R-000608

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	990	1140	1300	1470	1640	1810	1950	2100
<b>25</b>	990	1140	1300	1470	1640	1810	1950	2100
<b>20</b>	1060	1220	1400	1580	1760	1940	2090	2250
<b>5 LT</b>	1320	1520	1750	1970	2190	2420	2620	2810
<b>5 HT</b>	1060	1220	1400	1580	1760	1940	2090	2250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.