


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 9.0/70 - 16 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 106 A8 |
| LI/SS FREE ROLLING | 119 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 222 | RIM REC | W 7 |
| OD (MM) | 760 | ECE | E11-106R-004536 |
| SLR (MM) | 355 | PR | 10 |
| RC (MM) | 2285 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.40 |
|-------------------|-------------|
| 10 FR | 1905 |
| 25 FR | 1620 |
| 30 FR | 1525 |
| 40 FR | 1360 |
| 10 DW | 1330 |
| 25 DW | 1130 |
| 30 DW | 1065 |
| 40 DW | 950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.