

# RT 747 AGRO INDUSTRIAL

<b>TIRE SIZE</b>	<b>500/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 A8 ; 154 B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94016822	<b>RC (IN)</b>	155.5
<b>SW (IN)</b>	19.1	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	52.0	<b>RIM ALT</b>	DW 15 L ; DW 18 L
<b>SLR (IN)</b>	23.0	<b>ECE</b>	E11-106R-002988

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	44
30	3890	4790	5620	6540	7360	8270
25	4280	5280	6180	7190	8090	9090
20	4570	5640	6610	7690	8660	9730
15	4750	5850	6870	7980	8980	10100
5 CYC	6420	7910	9280	10780	12150	13650
STATIC	8980	11080	12980	15090	17000	19100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.