

AGRIMAX RT 855

TIRE SIZE	520/85 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	SPECIAL
TIRE TYPE	TL
LI/SS	158 A8/B



DIMENSÕES IS STANDARD

SW (MM)	516	RIM REC	DW 16 L; W 16 A; W 16 L; DD 16
OD (MM)	2052	RIM ALT	DW 18 L; W 18 L; W 18 A
SLR (MM)	930	ECE	E4-106R-001415
RC (MM)	6157	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	2340	2720	3105	3485	3870	4250
40	2340	2720	3105	3485	3870	4250
30	2505	2915	3325	3735	4145	4550
10 LT	3135	3645	4160	4670	5185	5695
10 HT	2505	2915	3325	3735	4145	4550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.