

# ARROW

|                     |                                     |
|---------------------|-------------------------------------|
| <b>TIRE SIZE</b>    | <b>9.00 - 20</b>                    |
| <b>UM</b>           | US STANDARD                         |
| <b>CONSTRUCTION</b> | ⊠ BIAS                              |
| <b>MACHINERY</b>    | REMORCĂ / MAȘINI DE<br>IMPLEMENTARE |
| <b>VERSION</b>      | STANDARD                            |
| <b>TIRE TYPE</b>    | TT                                  |



## DIMENSIUNI US STANDARD

|                 |          |                |          |
|-----------------|----------|----------------|----------|
| <b>USA CODE</b> | 94022489 | <b>RIM ALT</b> | 6.5; 7.5 |
| <b>SW (IN)</b>  | 10.6     | <b>PR</b>      | 14       |
| <b>OD (IN)</b>  | 40.9     |                |          |
| <b>RIM REC</b>  | 7.0      |                |          |

## LOAD CAPACITY (LBS/TIRE)

|                  |   |   |
|------------------|---|---|
| <b>MPH / PSI</b> | - | - |
| -                | - | - |
| -                | - | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.