


AGRIMAX V- FLECTO

TIRE SIZE	VF 750/70 R 44
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	186 D



РАЗМЕРЫ IS STANDARD

SW (MM)	760	RIM REC	DW 25 B
OD (MM)	2175	RIM ALT	DW 24 B
SLR (MM)	958	ECE	E11-106R-006765
RC (MM)	6450	SRI	1025

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	4325	5015	5710	6485	7180	7870	8645
FROM 65 TO 40	4750	5510	6270	7125	7885	8645	9500
30	4845	5625	6400	7270	8045	8820	9690
20	4940	5735	6525	7410	8205	8995	9880
10	5225	6065	6900	7840	8675	9510	10450
*UPTO 10 CYC WITH FRONT LOADER	6650	7715	8780	9975	11040	12105	13300
10HT	4845	5625	6400	7270	8045	8820	9690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.