

FLOTATION TR 675

TIRE SIZE	550/60 - 22.5
UM	US STANDARD
CONSTRUCTION	❖ BIAS
MACHINERY	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/156 B



РАЗМЕРЫ US STANDARD

USA CODE	94019809	RC (IN)	143.3
SW (IN)	21.7	RIM REC	AG 16.00
OD (IN)	49.6	ECE	E11-106R-004396
SLR (IN)	21.5	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	26	30
5 FR	11410	12690	13890
10 FR	10260	11420	12500
20 FR	9130	10150	11110
25 FR	8150	9060	9920
30 FR	7330	8160	8820
5 DW	7980	8880	9720
10 DW	7180	8000	8750
20 DW	6380	7110	7780
25 DW	5700	6350	6940
30 DW	5130	5710	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.