



IS standard



GROWING TOGETHER

# AT 621



PRODUCT DATA SHEET



Bias



# AT 621

AT 621 is suitable for backhoe loaders and compact loaders in all digging and loading operations in agriculture. The AT 621 tire features an extra deep tread which ensures great cut and chip resistance and higher durability. In addition, this BKT tire ensures great durability and self cleaning properties. AT 621 is available in several versions to meet the most differing user requirements.

## Performance



Durability



Traction



Self-Cleaning



Cut and Chip Resistance

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
<b>Ø 15"</b>	33 X 12.5 - 15	TT	8	-	-	STD	318	851	394	2507	10.00 F SDC	-
<b>Ø 15.3"</b>	10.0/75 - 15.3	TL	10	127 A6	-	STD	267	780	373	2385	9.0	-
<b>Ø 16"</b>	9.00 - 16	TT	16	137 A6	-	IND	260	925	-	-	6.50 H	6.00 G
	12.5/70 - 16	TL	8	-	-	STD	315	855	385	2584	10 LB	-
	12.5/70 - 16	TT	14	-	-	STD	315	855	385	2584	10 LB	-
	12.5/70 - 16	TL	14	-	-	STD	315	855	385	2584	10 LB	-
<b>Ø 18"</b>	12.5/80 - 18	TT	12	129 A8	142 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	12	129 A8	142 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	12	129 A8	142 A8	SPL	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	16	135 A8	148 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TT	16	135 A8	148 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	16	135 A8	148 A8	IND HD	308	987	434	2916	W 9	11.0
	15.5/60 - 18	TL	10	139 A2	-	STD	394	940	428	2871	W 13	-
	15.5/60 - 18	TL	12	141 A2	-	STD	394	940	428	2871	W 13	-
<b>15.5/70 - 18 (400/70 - 18)</b>	TL	10	-	-	-	STD	400	1030	474	3111	W 13	-

STD: Standard - IND: Industrial - SPL: Special - IND HD: Industrial Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



Performance



Durability



Traction



Self-Cleaning



Cut and Chip Resistance



	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 19.5"	385/65 D 19.5	TL	16	165 A2	STD	390	1020	478	3136	11.75	12.25
Ø 20"	12.5 - 20	TT	12	-	STD	325	1040	480	3103	11.0	-
	17.5/65 - 20	TL	10	-	STD	450	1090	490	3294	W 14 L	-
	42 X 17 - 20	TT	10	-	STD	432	1073	480	3198	14.00 TG SDC	-
	400/70 - 20	TL	16	152 B/ 168 A2	STD	405	1090	494	3271	13	12 SDC ; 13 SDC ; 14
	400/70 - 20	TL	-	149 A8	STD	405	1090	494	3271	13	12 SDC ; 13 SDC ; 14
Ø 24"	16.9 - 24	TL	12	149 A8	IND	450	1302	590	3906	DW 15 L	DW 14 L
	17.5 L - 24	TL	8	139 A8	STD	450	1255	558	3752	DW 15 L	DW 14 L
	19.5 L - 24	TL	12	151 A8	STD	482	1305	587	3936	DW 16 L	-
Ø 26"	18.4 - 26	TL	12	156 A8	STD	480	1425	649	4288	DW 16 L	DW 15 L
Ø 28"	16.9 - 28	TT	12	152 A8	IND	450	1410	639	4199	DW 15 L	DW 14 L
	16.9 - 28	TL	12	152 A8	IND	450	1410	639	4199	DW 15 L	DW 14 L
	16.9 - 28	TL	14	154 A8	IND	450	1410	639	4199	DW 15 L	DW 14 L
Ø 30"	16.9 - 30	TL	12	153 A8	IND	450	1460	670	4398	DW 15 L	DW 14 L

STD: Standard - IND: Industrial

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference