


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 420/65 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 135 D ; 138 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| CODE USA | 94052394 | RC (IN) | 150.6 |
| SW (IN) | 16.5 | RIM REC | W 13 |
| OD (IN) | 49.5 | RIM ALT | W 12; W 11 |
| SLR (IN) | 23.0 | ECE | E11-106R-002974 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 2260 | 2600 | 2990 | 3370 | 3760 | 4130 | 4480 | 4810 |
| 30 | 2380 | 2730 | 3130 | 3540 | 3950 | 4340 | 4700 | 5050 |
| 25 | 2450 | 2810 | 3230 | 3650 | 4070 | 4480 | 4840 | 5200 |
| 20 | 2600 | 3000 | 3440 | 3880 | 4320 | 4760 | 5150 | 5530 |
| 5 LT | 3030 | 3480 | 4000 | 4520 | 5040 | 5560 | 6010 | 6450 |
| 5 HT | 2600 | 3000 | 3440 | 3880 | 4320 | 4760 | 5150 | 5530 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.