

EARTHMAX SR 49



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 49

EARTHMAX SR 49 is an All Steel radial tyre that has been engineered for loaders and dozers, low profile dump trucks (LPDT) and load haul dumps (LHD). EARTHMAX SR 49 provides optimum performance in severe mining operations requiring exceptional traction and stability. The tyre has a directional pattern and is made of a special cut-resistant compound providing excellent durability.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø33"	35/65 R 33	TL	L4	**	224 A2	28.00/3.5	--	0	899	2061	890	6125	59	CR
	35/65 R33	TL	L4	***	229 A2	28.00/3.5	--	0	899	2061	890	6125	59	CR
	35/65 R 33	TL	SH4	****	-	28.00/3.5	--	0	899	2061	890	6125	59	CR
	35/65 R33	TL	E4/L4	****/***	-	28.00/3.5	--	0	899	2061	890	6125	59	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES					PERFORMANCES			
								
								
A2	245 kg							

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.D. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø45"	45/65 R 45	TL	L4	**	245 A2	36.00/4.5	-	0	1130	2730	1190	8113	72	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES				PERFORMANCES			
							
							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026