

# AT 603

<b>TIRE SIZE</b>	<b>12.5/80 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ARBETSFORDON / GRÄVLASTARE / ARBETSFORDON / GRÄVLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	135 A8
<b>LI/SS FREE ROLLING</b>	148 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	308	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	1000	<b>RIM ALT</b>	11
<b>SLR (MM)</b>	448	<b>ECE</b>	E11-106R-004351
<b>RC (MM)</b>	3027	<b>PR</b>	16

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>4.90</b>
10 FR	4410
25 FR	3750
30 FR	3530
40 FR	3150
10 DW	3050
25 DW	2595
30 DW	2440
40 DW	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.