


# TR 315

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>31X15.50 - 15</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |  BIAS                            |
| <b>MACHINERY</b>    | ATTREZZI AGRICOLI / MACCHINA PER<br>IL RACCOLTO DI FRUTTETI /<br>SCAVAFOSSI / MIETITREBBIA /<br>ATTREZZI AGRICOLI |
| <b>VERSIONE</b>     | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94043774 | <b>RC (IN)</b> | 98.3           |
| <b>SW (IN)</b>    | 15.4     | <b>RIM REC</b> | 13 LB          |
| <b>OD (IN)</b>    | 31.5     | <b>ECE</b>     | E4-106R-001553 |
| <b>SLR (IN)</b>   | 15.2     | <b>PR</b>      | 10             |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>60</b> |
| 30               | 3200      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.