

# AW 702

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>10.5/65 - 16</b>   |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | ❖ BIAS  |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / REMORQUE |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS FREE ROLLING</b> | 123 A8  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 270  | <b>RIM REC</b> | W 9             |
| <b>OD (MM)</b>  | 760  | <b>RIM ALT</b> | W 8; W 8 L      |
| <b>SLR (MM)</b> | 350  | <b>ECE</b>     | E11-106R-003513 |
| <b>RC (MM)</b>  | 2329 | <b>PR</b>      | 10              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.80</b> |
|-------------------|-------------|
| 10 FR             | 2170        |
| 25 FR             | 1845        |
| 30 FR             | 1735        |
| 40 FR             | 1550        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.