


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 600/60 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 D



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94059126	<b>RC (IN)</b>	200.0
<b>SW (IN)</b>	23.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	66.3	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	29.8	<b>ECE</b>	E11-106R-005021

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5200	6050	7010	7860	8710	9570	10630
<b>FROM 40 TO 25</b>	5720	6660	7700	8640	9580	10520	11700
20	5830	6790	7850	8810	9770	10720	11920
12	5940	6920	8000	8980	9950	10930	12150
5	6280	7320	8470	9500	10530	11560	12850
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	8000	9310	10780	12090	13400	14720	16360
5 HT	5830	6790	7850	8810	9770	10720	11920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.