

# MULTIMAX MP 527

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>440/80 R 28 IND</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |  RADIAL    |
| <b>MACHINERY</b>    | CARGADORA COMPACTA / ELEVADOR<br>TELESCÓPICO / CARGADORA<br>COMPACTA / ELEVADOR TELESCÓPICO |
| <b>VERSIÓN</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 156 A8/B  |



## DIMENSIONES IS STANDARD

|                 |      |                |                           |
|-----------------|------|----------------|---------------------------|
| <b>SW (MM)</b>  | 441  | <b>RIM REC</b> | DW 14 L                   |
| <b>OD (MM)</b>  | 1415 | <b>RIM ALT</b> | DW 13 ; DW 13 L ; DW 15 L |
| <b>SLR (MM)</b> | 648  | <b>ECE</b>     | E11-106R-002984           |
| <b>RC (MM)</b>  | 4270 | <b>SRI</b>     | 675                       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  | 3.4  | 3.6  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50         | 2300 | 2725 | 2940 | 3150 | 3360 | 3575 | 3790 | 4000 | -    | -    |
| 40         | 2300 | 2725 | 2940 | 3150 | 3360 | 3575 | 3790 | 4000 | -    | -    |
| 30         | 2480 | 2930 | 3155 | 3380 | 3605 | 3830 | 4055 | 4280 | -    | -    |
| 25         | 2570 | 3040 | 3270 | 3505 | 3740 | 3970 | 4205 | 4440 | -    | -    |
| 10 CYC.    | 2840 | 3470 | 3790 | 4105 | 4420 | 4735 | 5050 | 5370 | 5685 | 6000 |
| STATIC     | 4360 | 5330 | 5810 | 6295 | 6780 | 7265 | 7750 | 8230 | 8715 | 9200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.