


AGRIMAX FORCE



| | |
|---------------------|--|
| TIRE SIZE | IF 800/70 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / HIGH-POWER TRACTOR / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 186 D |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|---------------------------|
| USA CODE | 94073641 | RC (IN) | 252.0 |
| SW (IN) | 31.3 | RIM REC | DW 27 B |
| OD (IN) | 84.6 | RIM ALT | DW 25 B; DW 28 B; DW 30 B |
| SLR (IN) | 37.4 | ECE | E4-106R-002650 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 8950 | 10280 | 11810 | 13340 | 14860 | 16380 | 17910 | 19060 |
| FROM 40 TO 25 | 9840 | 11310 | 12980 | 14660 | 16340 | 18010 | 19690 | 20900 |
| 20 | 10230 | 11760 | 13500 | 15240 | 16990 | 18730 | 20470 | 21780 |
| 12 | 10630 | 12210 | 14020 | 15830 | 17640 | 19440 | 21250 | 22620 |
| 5 | 12500 | 14360 | 16490 | 18620 | 20740 | 22870 | 25000 | 26600 |
| UPTO 20 CYC | 12790 | 14690 | 16880 | 19060 | 21230 | 23410 | 25580 | 27230 |
| UPTO 10 CYC | 15260 | 17530 | 20120 | 22720 | 25320 | 27910 | 30510 | 32460 |
| UPTO 5 CYC | 16730 | 19220 | 22070 | 24920 | 27770 | 30610 | 33460 | 35600 |
| 5HT | 10230 | 11760 | 13500 | 15240 | 16990 | 18730 | 20470 | 21780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.