


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 710/60 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	708	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1614	<b>ECE</b>	E4-106R-001407
<b>SLR (MM)</b>	714	<b>SRI</b>	775
<b>RC (MM)</b>	4814	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2340	2695	3105	3460	3870	4225	4735	5095
<b>FROM 65 TO 40</b>	2575	2965	3415	3805	4255	4645	5205	5600
30	2675	3080	3550	3955	4425	4830	5410	5820
20	2780	3200	3685	4105	4595	5015	5620	6045
10	3270	3765	4335	4830	5400	5895	6610	7110
<b>UPTO 30 CYC</b>	3345	3850	4435	4945	5530	6035	6765	7280
<b>UPTO 15 CYC</b>	3990	4595	5290	5895	6595	7195	8065	8680
<b>UPTO 10 CYC</b>	4375	5040	5805	6465	7230	7895	8845	9520
10 HT	2675	3080	3550	3955	4425	4830	5410	5820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.