


AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 230/95 R 36 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 130 A8/B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94027477 | RC (IN) | 161.9 |
| SW (IN) | 9.0 | RIM REC | W 7 |
| OD (IN) | 53.2 | RIM ALT | W 8 |
| SLR (IN) | 25.2 | ECE | E4-106R-000765 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 64 |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 30 | 1640 | 2140 | 2600 | 2850 | 3020 | 3320 | 3600 | 3900 | 4180 | - |
| 25 | 1640 | 2140 | 2600 | 2850 | 3020 | 3320 | 3600 | 3900 | 4180 | - |
| 20 | 1750 | 2290 | 2790 | 3050 | 3240 | 3550 | 3870 | 4180 | 4490 | - |
| 5 | 1950 | 2460 | 3020 | 3580 | 4160 | 4280 | 4780 | 5280 | 5790 | 6280 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.