


# AGRIMAX RT 855

<b>TYRE SIZE</b>	<b>180/95 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	105 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94039210	<b>RC (IN)</b>	89.2
<b>SW (IN)</b>	7.3	<b>RIM REC</b>	5.5 F
<b>OD (IN)</b>	29.9	<b>RIM ALT</b>	6.0 F
<b>SLR (IN)</b>	13.4	<b>ECE</b>	E4-106R-000756

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	12	17	23	29	35	41	46	52
30	950	1210	1480	1620	1740	1910	2040	-
25	950	1210	1480	1620	1740	1910	2040	-
20	1010	1290	1580	1730	1860	2040	2180	-
5	1110	1440	1750	2090	2390	2490	2770	3060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.