

MULTIMAX MP 522

| | |
|---------------------|---|
| TIRE SIZE | 480/80 R 26 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CARGADORA COMPACTA / ELEVADOR TELESCÓPICO / CARGADORA COMPACTA / ELEVADOR TELESCÓPICO |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 167 A8/B |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94073108 | RC (IN) | 168.8 |
| SW (IN) | 18.9 | RIM REC | DW 15 L |
| OD (IN) | 56.2 | RIM ALT | DW 16 L |
| SLR (IN) | 25.1 | ECE | E11-106R-008146 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 46 | 49 | 52 | 55 | 58 | 61 | 64 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5680 | 6210 | 6730 | 7260 | 7800 | 8330 | 8860 | 9390 | 9920 | 10450 | 10970 | 11500 | 12010 | - | - |
| 25 | 5680 | 6210 | 6730 | 7260 | 7800 | 8330 | 8860 | 9390 | 9920 | 10450 | 10970 | 11500 | 12010 | - | - |
| 20 | 6150 | 6710 | 7270 | 7830 | 8390 | 8950 | 9510 | 10060 | 10630 | 11190 | 11750 | 12300 | 12860 | - | - |
| 15 | 6370 | 6960 | 7540 | 8110 | 8700 | 9280 | 9870 | 10440 | 11020 | 11610 | 12180 | 12760 | 13340 | - | - |
| 5 CYC. | 7050 | 7840 | 8620 | 9400 | 10180 | 10970 | 11750 | 12530 | 13320 | 14100 | 14880 | 16450 | 18020 | - | - |
| STATIC | 10800 | 12000 | 13200 | 14410 | 15610 | 16810 | 18010 | 19210 | 20410 | 21620 | 22820 | 24020 | 25230 | 26430 | 27630 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.