


# FL 639

<b>TIRE SIZE</b>	<b>710/40 R 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ESPARCIDOR / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 B ; 158 B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	727	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1140	<b>ECE</b>	E11-106R-006479
<b>SLR (MM)</b>	503	<b>SRI</b>	550
<b>RC (MM)</b>	3492		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
<b>50 FR</b>	2300	2650	3000	3325	3650	3950	4250	4560	4875	5235	5600	5800	6000
<b>50 DW</b>	1650	1885	2120	2345	2575	2785	3000	3225	3450	3725	4000	4125	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.