

AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 230/95 R 48 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 136 D ; 139 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94052837 | RC (IN) | 200.2 |
| SW (IN) | 9.0 | RIM REC | W 7 |
| OD (IN) | 65.2 | RIM ALT | W 8 |
| SLR (IN) | 31.2 | ECE | E11-106R-004067 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 40 | 1730 | 2030 | 2620 | 3160 | 3520 | 3700 | 4060 | 4400 | 4700 | 4940 |
| 30 | 1820 | 2140 | 2760 | 3330 | 3690 | 3900 | 4270 | 4630 | 4940 | 5190 |
| 25 | 1880 | 2200 | 2840 | 3440 | 3810 | 4020 | 4400 | 4770 | 5090 | 5360 |
| 20 | 2000 | 2340 | 3020 | 3650 | 4050 | 4270 | 4670 | 5070 | 5410 | 5690 |
| 5 | 2600 | 3040 | 3940 | 4750 | 5270 | 5560 | 6080 | 6600 | 7040 | 7410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.