

# AGRIMAX FORCE

|                  |                                             |
|------------------|---------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 650/85 R 42 CFO</b>                   |
| <b>UM</b>        | IS STANDARD                                 |
| <b>MACHINERY</b> | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR |
| <b>VERSION</b>   | STANDARD                                    |
| <b>TL/TT</b>     | TL                                          |
| <b>LI/SS</b>     | 180 D                                       |

## DIMENSIONS IS STANDARD

|                 |      |                 |                |
|-----------------|------|-----------------|----------------|
| <b>SW (MM)</b>  | 650  | <b>RIM REC</b>  | DW 23 B        |
| <b>OD (MM)</b>  | 2173 | <b>ECE</b>      | E4-106R-001832 |
| <b>SLR (MM)</b> | 965  | <b>SRI</b>      | 1025           |
| <b>RC (MM)</b>  | 6400 | <b>TRA CODE</b> | R1W            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1.0  | 1.2  | 1.4   | 1.6   | 2.0   | 2.4   |
|----------------------|------|------|------|------|-------|-------|-------|-------|
| <b>70</b>            | 3420 | 3930 | 4510 | 5095 | 5675  | 6260  | 6840  | 7280  |
| <b>FROM 65 TO 40</b> | 3760 | 4320 | 4960 | 5600 | 6240  | 6880  | 7520  | 8000  |
| <b>30</b>            | 3910 | 4490 | 5155 | 5820 | 6485  | 7155  | 7820  | 8320  |
| <b>20</b>            | 4060 | 4665 | 5355 | 6045 | 6735  | 7430  | 8120  | 8640  |
| <b>10</b>            | 4775 | 5485 | 6295 | 7110 | 7920  | 8735  | 9550  | 10160 |
| <b>UPTO 30 CYC</b>   | 4885 | 5615 | 6445 | 7280 | 8110  | 8940  | 9775  | 10400 |
| <b>UPTO 15 CYC</b>   | 5825 | 6695 | 7685 | 8680 | 9670  | 10660 | 11655 | 12400 |
| <b>UPTO 10 CYC</b>   | 6390 | 7340 | 8430 | 9520 | 10605 | 11695 | 12780 | 13600 |
| <b>10 HT</b>         | 3910 | 4490 | 5155 | 5820 | 6485  | 7155  | 7820  | 8320  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

