

# AT 621

<b>TIRE SIZE</b>	<b>12.5/80 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	CARREGADORA COMPACTA / RETROESCAVADORA / RETROESCAVADORA / CARREGADORA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	129 A8
<b>LI/SS FREE ROLLING</b>	142 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94019731	<b>RC (IN)</b>	114.8
<b>SW (IN)</b>	12.1	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	38.9	<b>RIM ALT</b>	11.0
<b>SLR (IN)</b>	17.1	<b>ECE</b>	E11-106R-003388

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840
5 DW	5710
15 DW	4850
20 DW	4560
25 DW	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.