


AGRIMAX SPARGO

TIRE SIZE	VF 750/60 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSIÓN	STEEL BELTED
TIRE TYPE	TL
LI/SS	189 D



DIMENSIONES US STANDARD

CÓDIGO USA	94075652	RC (IN)	249.5
SW (IN)	29.7	RIM REC	DW27B
OD (IN)	82.1	ECE	E11-106R-009075
SLR (IN)	37.0	TRA CODE	R1

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	46
45	12180	13450	14920	15760	16590	17230	17860	18700	19540	20280	21000
FROM 40 TO 25	13180	14540	16130	17030	17950	18630	19310	20220	21120	21920	22710
20	13450	14840	16460	17390	18310	19010	19700	20630	21550	22370	23170
12	13710	15130	16780	17730	18670	19380	20090	21040	21970	22800	23630
5	14500	16000	17740	18740	19750	20500	21250	22240	23240	24110	24980

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.