

# CON STAR

|                     |                                 |
|---------------------|---------------------------------|
| <b>TYRE SIZE</b>    | <b>340/80 - 18</b>              |
| <b>UM</b>           | US STANDARD                     |
| <b>CONSTRUCTION</b> | ⊠ BIAS                          |
| <b>MACHINERY</b>    | COMPACT LOADER / COMPACT LOADER |
| <b>VERSION</b>      | INDUSTRIAL                      |
| <b>TYRE TYPE</b>    | TL                              |
| <b>LI/SS</b>        | 143 A8                          |



## DIMENSIONS US STANDARD

|                 |          |                |                                |
|-----------------|----------|----------------|--------------------------------|
| <b>USA CODE</b> | 94051304 | <b>RC (IN)</b> | 119.7                          |
| <b>SW (IN)</b>  | 13.8     | <b>RIM REC</b> | 11                             |
| <b>OD (IN)</b>  | 40.0     | <b>RIM ALT</b> | 12; 11 SDC; 12 SDC; W 10; W 11 |
| <b>SLR (IN)</b> | 18.3     | <b>ECE</b>     | E11-106R-003020                |

## LOAD CAPACITY (LBS/TYRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>58</b> |
| 25               | 6010      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.