DATA SHEET

PRINTED ON
21-04-2026

AS 504

TIRE SIZE	**16.0/70 - 20**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	144 A8
LI/SS FREE ROLLING	156 A8

ABMESSUNGEN US STANDARD

USA-CODE	94032808	**RC (IN)**	126.5
SW (IN)	16.5	**RIM REC**	13
OD (IN)	43.2	**RIM ALT**	12 SDC; 14; 13 SDC
SLR (IN)	19.2	**ECE**	E11-106R-004611

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	12350
15 FR	10490
20 FR	9880
25 FR	8820
5 DW	8640
15 DW	7340
20 DW	6910
25 DW	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..