

# AGRIMAX RT 765

|              |                                                                                             |
|--------------|---------------------------------------------------------------------------------------------|
| TIRE SIZE    | 420/70 R 24                                                                                 |
| UM           | IS STANDARD                                                                                 |
| CONSTRUCTION |  RADIAL    |
| MACHINERY    | PULVÉRISATEUR / TRACTEUR /<br>MACHINE À VENDANGER /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE |
| VERSION      | STANDARD                                                                                    |
| TIRE TYPE    | TL                                                                                          |
| LI/SS        | 130 D                                                                                       |



## DIMENSIONS IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 418  | RIM REC | W 13            |
| OD (MM)  | 1248 | RIM ALT | W 12 ; W 14 L   |
| SLR (MM) | 554  | ECE     | E11-106R-005826 |
| RC (MM)  | 3680 | SRI     | 600             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 1045 | 1220 | 1390 | 1560 | 1730 | 1900 |
| 50         | 1100 | 1280 | 1460 | 1640 | 1820 | 1995 |
| 40         | 1150 | 1335 | 1525 | 1710 | 1900 | 2085 |
| 30         | 1205 | 1400 | 1600 | 1795 | 1990 | 2185 |
| 10 LT      | 1405 | 1635 | 1865 | 2095 | 2325 | 2550 |
| 10 HT      | 1205 | 1400 | 1600 | 1795 | 1990 | 2185 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.