


AGRIMAX SPARGO SB

| | |
|---------------------|--|
| TYRE SIZE | VF 380/90 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STEEL BELTED |
| TYRE TYPE | TL |
| LI/SS | 173 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94076123 | RC (IN) | 223.1 |
| SW (IN) | 15.7 | RIM REC | W13 |
| OD (IN) | 72.9 | RIM ALT | W12;DW13 |
| SLR (IN) | 33.7 | ECE | E11-106R-0010176 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 14 | 12 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 47 | 49 | 52 | 55 | 58 | 61 | 64 |
|---------------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5620 | 6270 | 7050 | 7700 | 8100 | 8480 | 8750 | 9010 | 9460 | 9930 | 10310 | 10710 | 11030 | 11360 | 11680 | 12010 | 12530 | 13040 |
| FROM 40 TO 25 | 6170 | 6880 | 7740 | 8460 | 8890 | 9320 | 9610 | 9890 | 10400 | 10900 | 11330 | 11750 | 12120 | 12470 | 12840 | 13190 | 13760 | 14330 |
| 20 | 6300 | 7030 | 7910 | 8640 | 9080 | 9510 | 9800 | 10090 | 10610 | 11120 | 11560 | 12000 | 12360 | 12720 | 13090 | 13450 | 14040 | 14620 |
| 12 | 6420 | 7160 | 8060 | 8800 | 9250 | 9690 | 9990 | 10290 | 10820 | 11340 | 11790 | 12230 | 12600 | 12980 | 13350 | 13720 | 14310 | 14910 |
| 5 | 6780 | 7580 | 8530 | 9310 | 9780 | 10260 | 10580 | 10880 | 11440 | 11990 | 12460 | 12930 | 13330 | 13730 | 14110 | 14510 | 15140 | 15770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.