


# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>380/90 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAŞINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	380	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1852	<b>RIM ALT</b>	W 11; W 13
<b>SLR (MM)</b>	859	<b>ECE</b>	E4-106R-001409
<b>RC (MM)</b>	5699	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1785	2290	2790	3065	3295	3605	3875	4070	4375	-
40	1785	2290	2790	3065	3295	3605	3875	4070	4375	-
30	1910	2450	2990	3280	3530	3860	4150	4360	4685	-
10	2095	2735	3315	3955	4540	4715	5235	5815	6040	6565

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.