DATA SHEET

PRINTED ON
22-04-2026

AS 504

TIRE SIZE	**7.00 - 12**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	SOLLEVATORE TELESCOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	75 A8
LI/SS FREE ROLLING	88 A8

DIMENSIONI US STANDARD

CODICE USA	94019236	**RC (IN)**	80.7
SW (IN)	7.4	**RIM REC**	4.5
OD (IN)	26.9	**ECE**	E4-106R-002207
SLR (IN)	12.2	**PR**	4

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	25
5 FR	1730
15 FR	1470
20 FR	1380
25 FR	1230
5 DW	1190
15 DW	1010
20 DW	950
25 DW	850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..