

# TF 9090

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>9.00 - 16</b>                        |
| <b>UM</b>           | IS STANDARD                             |
| <b>CONSTRUCTION</b> | BIAS                                    |
| <b>MACHINERY</b>    | MICRO TRACTEUR / TRACTEUR /<br>REMORQUE |
| <b>VERSION</b>      | SPECIAL                                 |
| <b>TIRE TYPE</b>    | TT                                      |
| <b>LI/SS</b>        | 116 A6                                  |



## DIMENSIONS IS STANDARD

|                 |      |                |                    |
|-----------------|------|----------------|--------------------|
| <b>SW (MM)</b>  | 257  | <b>RIM REC</b> | W 8                |
| <b>OD (MM)</b>  | 855  | <b>RIM ALT</b> | 6.00 F; W 7; W 8 L |
| <b>SLR (MM)</b> | 398  | <b>ECE</b>     | E11-106R-004114    |
| <b>RC (MM)</b>  | 2548 | <b>PR</b>      | 10                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.90</b> |
| 30                | 1250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.