


# AS 504

<b>TIRE SIZE</b>	<b>6.00 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	HD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	83 A8
<b>LI/SS FREE ROLLING</b>	95 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94053346	<b>RC (IN)</b>	86.2
<b>SW (IN)</b>	6.5	<b>RIM REC</b>	4.00 E
<b>OD (IN)</b>	28.9	<b>RIM ALT</b>	4.50 E; 4½ K
<b>SLR (IN)</b>	13.5	<b>ECE</b>	E11-106R-005194

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	2130
15 FR	1810
20 FR	1710
25 FR	1520
5 DW	1500
15 DW	1270
20 DW	1200
25 DW	1070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.