

# TR 390

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 23.1 - 26  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | ПРИЦЕП /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ /<br>УПЛОТНИТЕЛЬНАЯ ТЕХНИКА |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 149 A8   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94005185 | <b>RC (IN)</b> | 178.9          |
| <b>SW (IN)</b>  | 23.4     | <b>RIM REC</b> | DW 20 B        |
| <b>OD (IN)</b>  | 61.4     | <b>ECE</b>     | E4-106R-002317 |
| <b>SLR (IN)</b> | 27.2     | <b>PR</b>      | 12             |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>24</b> |
| 25               | 7150      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.