


# AS 504

<b>TYRE SIZE</b>	<b>7.00 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	83 A8
<b>LI/SS FREE ROLLING</b>	95 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94019267	<b>RC (IN)</b>	78.8
<b>SW (IN)</b>	7.4	<b>RIM REC</b>	4.5
<b>OD (IN)</b>	26.9	<b>PR</b>	6
<b>SLR (IN)</b>	11.8		

## LOAD CAPACITY (LBS/TYRE)

<b>MPH / PSI</b>	<b>36</b>
<b>5 FR</b>	2130
<b>15 FR</b>	1810
<b>20 FR</b>	1710
<b>25 FR</b>	1520
<b>5 DW</b>	1500
<b>15 DW</b>	1270
<b>20 DW</b>	1200
<b>25 DW</b>	1070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.